

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number
WO 01/17918 A1

(51) International Patent Classification?: C03B 37/014,
19/14

(72) Inventor; and

(75) Inventor/Applicant (for US only): SARKAR, Arnab
[US/US]; 6715 Daryn Drive, West Hills, CA 91307 (US).

(21) International Application Number: PCT/US00/24456

(22) International Filing Date:
1 September 2000 (01.09.2000)

(74) Agent: BRUEGGEMANN, James, R.; Sheppard, Mullin,
Richter & Hampton LLP, 48th floor, 333 South Hope Street,
Los Angeles, CA 90071 (US).

(25) Filing Language: English

(81) Designated States (national): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,
UG, US, UZ, VN, YU, ZA, ZW.

(26) Publication Language: English


(30) Priority Data:
60/152,293 3 September 1999 (03.09.1999) US

(71) Applicant (for all designated States except US): BULAR,
LLC [US/US]; 6715 Daryn Drive, West Hills, CA 91307
(US).

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: APPARATUS FOR MAKING A GLASS PREFORM BY FLAME HYDROLYSIS



(57) Abstract: An apparatus is described, for making a glass preform by flame hydrolysis. The apparatus includes a main deposition burner configured to direct two or more streams of soot-forming reactants and a stream of flame gases into a deposition chamber, in a direction toward a rotating support mandrel, so as to form by flame hydrolysis a glass preform on the mandrel. One or more pairs of auxiliary burners may also be included, for introducing further streams of flame gases, but no streams of soot-forming reactants, toward the glass preform, from opposite lateral sides of the main deposition burner; to provide additional heat when the preform has reached a predetermined size, thereby improving efficiency. The main deposition burner is configured to direct the two or more of the streams of soot-forming reactants to impinge quasi-tangentially toward the mandrel and, further, to direct the stream of flame gases obliquely inwardly toward the two or more streams of soot-forming reactants, to narrow the flame's width along one or both of two orthogonal axes.



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *With international search report.*